

PRODUCT SPECIFICATIONS:

6100 SERIES (VINYL FABRICS)

WIDTH: 54"
PUT UP: 25 YDS. R.O.T.
WEIGHT: 19.57 OZ/SQ. YD.
29.355 @ 54"

COMPOSITION: 13 MIL Printed PVC Film,
Laminated to a 4 oz. per sq. yd.
non-woven with upholstery
grade foam

		<u>RESULTS</u>	
CROCKING	DRY	PASS	CFFA CRITERIA
CFFA 7	H2O	PASS	INDOOR UPHOLSTERY
	ALCOHOL	PASS	
	409	PASS	
BLOCKING (FFFA 4)		PASS	
180°F @ 1/2 hour			
FABRIC BOND(CFFA3)			
	MD	8 LBS	4 LBS
	TD	11 LBS	4 LBS
SEAM STRENGTH (CFFA14)			
	MD	68 LBS	45 LBS
	TD	77 LBS	45 LBS
TRAP TEAR (CFFA A16C)			
	MD	48 LBS	20 LBS
	TD	30 LBS	20 LBS
GRAB TENSILE (CFFA 17)			
	MD	138 LBS	75 LBS
	TD	143 LBS	75 LBS
COLD CRACK (CFFA 6A3) 0°F		10# ROLLER 2 HOURS	
	MD	NO CRACKING	NO CRACKING
	TD	NO CRACKING	NO CRACKING
FLAME (MVSS-302)		PASS	
FLAME (CAL,17,SECTION E)		PASS	
NEWARK FLEX (CFFA 10) 25,000 CYCLES			
	MD	PASS	
	TD	PASS	
WYZENBEEK (CFFA-1A)		PASS (No Print Loss)	
ABRADANT, STEEL SCREEN WIRE			
60,000 CYCLES ABRASION			
2 LBS. PRESSION, 6 LBS. TENSION			
WYZENBEEK (ASTM-D-3597.02)		PASS (No Print Loss)	
ABRADANT, COTTON DUCK			
400,000 CYCLES			